RECEIVED
CENTRAL FAX CENTER

01/31/2006 17:36 FAX 312 427 6663

LADAS & PARRY LLP

JAN 3 1 2006

Ø 001

Application Serial No. 10/811,728
Revised Appeal Brief dated January 31, 2006

PATENT

DOCKET: CU-3663

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:

Hiroyuki TAKAMURA

SERIAL NO:

10/811,728

) Group Art Unit: 3748

FILED:

March 29, 2004

) Examiner: Ching CHANG

TITLE:

VALVE TRAIN FOR INTERNAL COMBUSTION ENGINE

Certification under 37 C.F.R. §1.8(b)

The USPTO Central Fax No. (571) 273-8300 Date of Fax Transmittal: January 31, 2006

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted to the United States Patent and Trademark Office to the fax number and on the date indicated above.

Brian W. Hameder, Reg. No. 45,613

Mail Stop Appeal Briefs – Patent Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

REVISED APPEAL BRIEF

Sir:

In response to the Notification of Non-Compliant Appeal Brief under 37 CFR 41.37 which issued on January 23, 2006, submitted herewith are three (3) copies of Appellant Revised Appeal Brief with respect to the Appeal taken to the Board of Patent Appeals and Interferences in the above-identified application.

The Notification of Non-Compliant Appeal Brief indicated that the Appeal Brief was defective under 37 CFR 41.37 (c)(1)(vi) for not containing a concise statement of each ground for rejection presented for review. The Appellant has revised the Appeal Brief to replace the —Issues— section heading with a "Grounds of Rejection to be Reviewed on Appeal" section heading.

PATENT DOCKET: CU-3663

Real Party in Interest

The real party in interest is Nippon Piston Ring Co., Ltd. to which full and exclusive interest in the invention of the present application has been assigned. The Assignment, executed March 30, 2004, is recorded in the U.S. Patent and Trademark Office at Reel 014899, Frame 0033.

Related Appeals and Interferences

There are no related appeals or interferences which are believed to directly affect or be directly affected by, or have a bearing on, the Board's decision in the present appeal.

Status of Claims

Claim 1 is pending and appealed. The text of the claims is presented in the Appendix.

Status of Amendments

There are no outstanding amendments. In the Advisory Action issued on July 25, 2005, the amendment to the claims dated July 13, 2005 is indicated as entered for purposes of appeal.

Summary of the Invention

The present application is directed to a valve train in an internal combustion engine having a cam lobe and a roller follower in rotational contact with one another (depicted in Figures 1-3 and 8). The cam lobe is made of a sintered material (Page 4, lines 5-100). The outer circumferential surfaces of both the cam lobe and the roller follower have a surface roughness R_a of 0.4 to 2.2 μ m (Page 4, lines 16-25).

Grounds of Rejection to be Reviewed on Appeal

1. Whether Claim 1 is properly rejected under 35 U.S.C. §103(a) as being unpatentable over Sada (U.S. Patent No. 5,997,988) in view of Nishioka et al. (U.S. Patent No. 6,367,439)?

Grouping of Claims

Claim 1 is the only pending claim.

PATENT DOCKET: CU-3663

Argument

Claim 1 is presently rejected under 35 U.S.C. §103(a) as being unpatentable over Sada in view of Nishioka et al. The Applicant respectfully traverses this rejection and submits that Claim 1 is patentable in view of these relied upon cited references.

The Examiner contends that 'the Sada reference discloses "the present invention is applicable to all machine parts each having a contact surface which enters a state of at least one of rolling contact and sliding contact with the other part opposite thereto" (See Col. 5, line 36 through line 39); and the contact surface having a maximum circumference surface roughness in 1.4 or 1.1 µm (See Table 1). Accordingly, the Examiner deems that the Sada reference teaches each of the cam lobe and the roller in Claim 1, having the claimed subject matter of surface roughness 0.4 to 2.2 µm.' (See the Advisory Action issued July 25, 2005 – Continuation Sheet of 11.). In contrast, the Applicant contends that Sada does not disclose or suggest both machine parts (cam lobe and roller follower) contact surfaces having a <u>surface roughness R_a of 0.4 to 2.2 µm</u>, as claimed.

Table 1 of Sada, on which the Examiner's arguments depend, set forth several embodiments and comparative examples, two of which, embodiment 1 and embodiment 2, disclose a maximum surface roughness Ry on one of the machine part contact surfaces as 1.4 or 1.1 µm. Table 1 does not, however, disclose both machine parts having contact surfaces with these maximum surface roughnesses, or within the claimed R_π surface roughness range of 0.4 to 2.2 μm, as explained in Column 6, line 57 through Column 7, line 11. That excerpt of the reference defines the test set-up that produced the results in Table 1 and clearly indicates that the other machine part has a surface roughness maximum height R_v which equals 3 µm, which is well beyond the claimed range, even if the maximum height Ry surface roughness is the same as the claimed Ra surface roughness, as the Examiner contends and the Applicant disputes. Without question, Sada does not disclose both machine parts having the specified surface roughness, as claimed. The Examiner has gone beyond the disclosure of the reference, and has used improper hindsight, in the assertion that it would have been obvious to provide both machine parts with the claimed surface roughness. This improper assertion of obviousness is even more so in light of the fact that the machine parts in the Sada reference are intended

PATENT DOCKET: CU-3663

to function differently than the cam lobe and follower of the present invention, which will be discussed in more detail later in this argument.

As referred to above, the Examiner also contends that the disclosed maximum height surface roughness R_y in Sada is equivalent to the claimed surface roughness R_a , which is well understood by persons skilled in the art to be the arithmetic mean surface roughness. In support of the Applicant's assertion of the well known definition of R_a , Applicant previously submitted an English translation of Japanese Industrial Standard B 0601 which defines R_a as the arithmetic mean roughness. As shown in Figure 9 of JIS B 0601, R_a is the average of a series of consecutive peak to valley vertical distances over a sample length of a surface. This value of R_a necessarily would be less than R_y which is defined in Sada as the vertical distance between the greatest peak height and the greatest valley height over a sample length of a surface, as shown in Figure 1 of Sada. Thus, Sada does not disclose the claimed R_a surface roughness values.

Also, as referred to above with regard to the function of the invention disclosed in Sada, the function of the prescribed surface roughness is to obtain an oil film controlled by the small recesses in the surface of the machine parts. This purpose is a function of the maximum height R_y surface roughness which is dependent upon and limited by the ratio of the peak height R_p and the valley depth R_v (R_p/R_v , See Figure 1 in Sada). Sada further describes that invention as being applicable to both rolling contact and sliding contact. The goal of that invention is to reduce wear on the machine parts by the formation of the oil film. In contrast, the function of the present invention is to provide only rolling contact between two machine parts without the formation of an oil film. From the stated purpose and function of Sada, the Applicant contends that there would be no motivation to further modify the invention of Sada to perform a different function. No disclosure, teaching or suggestion of such a modification of the function of the device is present, let alone the claimed features of both machine parts having a specified surface roughness.

The Applicant further considers that even if $R_{\mathfrak{p}}$ of the present application were equal to $R_{\mathfrak{p}}$ of Sada, that Sada teaches away from using the claimed surface roughness, notwithstanding the fact that Sada teaches $R_{\mathfrak{p}}$ equals 3 μm on the second machine part contact surface. Table 1 in Sada shows a $R_{\mathfrak{p}}$ value in comparative example 3 within the assumed claimed range that yields a negative result, and a $R_{\mathfrak{p}}$ value in embodiment 3 outside the assumed claimed range that

PATENT DOCKET: CU-3663

yields a positive result. This is completely contradictory to the two examples chosen by the Examiner, and further emphasizes that for the purposes of the invention of Sada, Ry is not the determinative value. That being the case, Sada would teach away from the present Claim 1 if both functioned in the same way to produce the same result.

With regard to the cited reference Nishioka et al., this reference is relied upon to provide an example in the prior art where a sintered material is used to manufacture machine parts. This reference is not relied upon by the Examiner, nor considered by the Applicant, to disclose the claimed features of both the cam lobe and roller follower having the prescribed surface roughness of R_s.

Conclusion

For the reasons given above, the Appellant respectfully submits that neither the relied upon cited references of Sada and Nishioka et al. disclose, teach or suggest the claimed features of both the cam lobe and roller follower having a surface roughness R_a of 0.4 to 2.2 μm . The Appellant thus considers that the Examiner has not met the burden required under 35 U.S.C. §103(a) of proving obviousness in view of these references. Accordingly, the Appellant respectfully requests the Board to reverse the Examiner's rejection of Claim 1, and requests allowance of the application.

<u>Jaпuary 31, 2006</u> Date

Attorney for Applicant Brian W. Hameder c/o Ladas & Parry LLP 224 South Michigan Avenue

Respectfully submitted,

Chicago, Illinois 60604 (312) 427-1300 Reg. No. 45613

PATENT DOCKET: CU-3663

APPENDIX

Listing of Claims:

- 1. (previously amended) A valve train for an internal combustion engine comprising a cam lobe fixed on a cam shaft and a roller follower provided with a roller to come in rotation-contact with the cam lobe, wherein the cam lobe is made of an iron based sintered material, and the surface roughness R_a of the outer circumferential surface thereof is 0.4 to 2.2 μ m, and the surface roughness R_a of the outer circumferential surface of the roller is 0.4 to 2.2 μ m.
- 2. (cancelled)
- 3. (cancelled)
- 4. (cancelled)

RECEIVED
CENTRAL FAX CENTER

Ø 007

JAN 3 1 2006 PATENT DOCKET: CU-3663

Application Serial No. 10/811,728 Revised Appeal Brief dated January 31, 2006

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:

Hiroyuki TAKAMURA

SERIAL NO:

10/811,728

Group Art Unit: 3748

FILED:

March 29, 2004

) Examiner: Ching CHANG

TITLE:

VALVE TRAIN FOR INTERNAL COMBUSTION ENGINE

Certification under 37 C.F.R. §1.8(b)

The USPTO Central Fax No. (571) 273-8300 Date of Fax Transmittal: January 31, 2006

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted to the United States Patent and Trademark Office to

the fax number and on the date indicated above,

Brian W. Hameder, Reg. No. 45,613

Mail Stop Appeal Briefs – Patent Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

REVISED APPEAL BRIEF

Sir:

In response to the Notification of Non-Compliant Appeal Brief under 37 CFR 41.37 which issued on January 23, 2006, submitted herewith are three (3) copies of Appellant Revised Appeal Brief with respect to the Appeal taken to the Board of Patent Appeals and Interferences In the above-identified application.

The Notification of Non-Compliant Appeal Brief indicated that the Appeal Brief was defective under 37 CFR 41.37 (c)(1)(vi) for not containing a concise statement of each ground for rejection presented for review. The Appellant has revised the Appeal Brief to replace the —Issues— section heading with a "Grounds of Rejection to be Reviewed on Appeal" section heading.

PATENT DOCKET: CU-3663

Real Party in Interest

The real party in interest is Nippon Piston Ring Co., Ltd. to which full and exclusive interest in the invention of the present application has been assigned. The Assignment, executed March 30, 2004, is recorded in the U.S. Patent and Trademark Office at Reel 014899, Frame 0033.

Related Appeals and Interferences

There are no related appeals or interferences which are believed to directly affect or be directly affected by, or have a bearing on, the Board's decision in the present appeal.

Status of Claims

Claim 1 is pending and appealed. The text of the claims is presented in the Appendix.

Status of Amendments

There are no outstanding amendments. In the Advisory Action issued on July 25, 2005, the amendment to the claims dated July 13, 2005 is indicated as entered for purposes of appeal.

Summary of the Invention

The present application is directed to a valve train in an internal combustion engine having a cam lobe and a roller follower in rotational contact with one another (depicted in Figures 1-3 and 8). The cam lobe is made of a sintered material (Page 4, lines 5-100). The outer circumferential surfaces of both the cam lobe and the roller follower have a surface roughness R_a of 0.4 to 2.2 μ m (Page 4, lines 16-25).

Grounds of Rejection to be Reviewed on Appeal

1. Whether Claim 1 is properly rejected under 35 U.S.C. §103(a) as being unpatentable over Sada (U.S. Patent No. 5,997,988) in view of Nishioka et al. (U.S. Patent No. 6,367,439)?

Grouping of Claims

Claim 1 is the only pending claim.

PATENT DOCKET: CU-3663

Argument

Claim 1 is presently rejected under 35 U.S.C. §103(a) as being unpatentable over Sada in view of Nishioka et al. The Applicant respectfully traverses this rejection and submits that Claim 1 is patentable in view of these relied upon cited references.

The Examiner contends that 'the Sada reference discloses "the present invention is applicable to all machine parts each having a contact surface which enters a state of at least one of rolling contact and sliding contact with the other part opposite thereto" (See Col. 5, line 36 through line 39), and the contact surface having a maximum circumference surface roughness in 1.4 or 1.1 µm (See Table 1). Accordingly, the Examiner deems that the Sada reference teaches each of the cam lobe and the roller in Claim 1, having the claimed subject matter of surface roughness 0.4 to 2.2 µm.' (See the Advisory Action issued July 25, 2005 — Continuation Sheet of 11.). In contrast, the Applicant contends that Sada does not disclose or suggest both machine parts (cam lobe and roller follower) contact surfaces having a surface roughness R_a of 0.4 to 2.2 µm, as claimed.

Table 1 of Sada, on which the Examiner's arguments depend, set forth several embodiments and comparative examples, two of which, embodiment 1 and embodiment 2, disclose a maximum surface roughness Ry on one of the machine part contact surfaces as 1.4 or 1.1 µm. Table 1 does not, however, disclose both machine parts having contact surfaces with these maximum surface roughnesses, or within the claimed R_a surface roughness range of 0.4 to 2.2 μm, as explained in Column 6, line 57 through Column 7, line 11. That excerpt of the reference defines the test set-up that produced the results in Table 1 and clearly indicates that the other machine part has a surface roughness maximum height Ry which equals 3 µm, which is well beyond the claimed range, even if the maximum height Ry surface roughness is the same as the claimed Ra surface roughness, as the Examiner contends and the Applicant disputes. Without question, Sada does not disclose both machine parts having the specified surface roughness, as claimed. The Examiner has gone beyond the disclosure of the reference, and has used improper hindsight, in the assertion that it would have been obvious to provide both machine parts with the claimed surface roughness. This improper assertion of obviousness is even more so in light of the fact that the machine parts in the Sada reference are intended

PATENT DOCKET: CU-3663

to function differently than the cam lobe and follower of the present invention, which will be discussed in more detail later in this argument.

As referred to above, the Examiner also contends that the disclosed maximum height surface roughness R_y in Sada is equivalent to the claimed surface roughness R_a , which is well understood by persons skilled in the art to be the arithmetic mean surface roughness. In support of the Applicant's assertion of the well known definition of R_a , Applicant previously submitted an English translation of Japanese Industrial Standard B 0601 which defines R_a as the arithmetic mean roughness. As shown in Figure 9 of JIS B 0601, R_a is the average of a series of consecutive peak to valley vertical distances over a sample length of a surface. This value of R_a necessarily would be less than R_y which is defined in Sada as the vertical distance between the greatest peak height and the greatest valley height over a sample length of a surface, as shown in Figure 1 of Sada. Thus, Sada does not disclose the claimed R_a surface roughness values.

Also, as referred to above with regard to the function of the invention disclosed in Sada, the function of the prescribed surface roughness is to obtain an oil film controlled by the small recesses in the surface of the machine parts. This purpose is a function of the maximum height R_y surface roughness which is dependent upon and limited by the ratio of the peak height R_p and the valley depth R_v (R_p/R_v , See Figure 1 in Sada). Sada further describes that invention as being applicable to both rolling contact and sliding contact. The goal of that invention is to reduce wear on the machine parts by the formation of the oil film. In contrast, the function of the present invention is to provide only rolling contact between two machine parts without the formation of an oil film. From the stated purpose and function of Sada, the Applicant contends that there would be no motivation to further modify the invention of Sada to perform a different function. No disclosure, teaching or suggestion of such a modification of the function of the device is present, let alone the claimed features of both machine parts having a specified surface roughness.

The Applicant further considers that even if R_a of the present application were equal to R_y of Sada, that Sada teaches away from using the claimed surface roughness, notwithstanding the fact that Sada teaches R_y equals 3 μ m on the second machine part contact surface. Table 1 in Sada shows a R_y value in comparative example 3 within the assumed claimed range that yields a negative result, and a R_y value in embodiment 3 outside the assumed claimed range that

PATENT DOCKET: CU-3663

yields a positive result. This is completely contradictory to the two examples chosen by the Examiner, and further emphasizes that for the purposes of the invention of Sada, R_y is not the determinative value. That being the case, Sada would teach away from the present Claim 1 if both functioned in the same way to produce the same result.

With regard to the cited reference Nishioka et al., this reference is relied upon to provide an example in the prior art where a sintered material is used to manufacture machine parts. This reference is not relied upon by the Examiner, nor considered by the Applicant, to disclose the claimed features of both the cam lobe and roller follower having the prescribed surface roughness of R_a.

Conclusion

For the reasons given above, the Appellant respectfully submits that neither the relied upon cited references of Sada and Nishioka et al. disclose, teach or suggest the claimed features of both the cam lobe and roller follower having a surface roughness R_a of 0.4 to 2.2 μm . The Appellant thus considers that the Examiner has not met the burden required under 35 U.S.C. §103(a) of proving obviousness in view of these references. Accordingly, the Appellant respectfully requests the Board to reverse the Examiner's rejection of Claim 1, and requests allowance of the application.

January 31, 2006 Date

Attorney for Applicant Brian W. Hameder c/o Ladas & Parry LLP 224 South Michigan Avenue Chicago, Illinois 60604 (312) 427-1300

Respectfully submitted,

Reg. No. 45613

PATENT DOCKET: CU-3663

APPENDIX

Listing of Claims:

- 1. (previously amended) A valve train for an internal combustion engine comprising a cam lobe fixed on a cam shaft and a roller follower provided with a roller to come in rotation-contact with the cam lobe, wherein the cam lobe is made of an iron based sintered material, and the surface roughness R_a of the outer circumferential surface thereof is 0.4 to 2.2 μ m, and the surface roughness R_a of the outer circumferential surface of the roller is 0.4 to 2.2 μ m.
- 2. (cancelled)
- 3. (cancelled)
- 4. (cancelled)

RECEIVED
CENTRAL FAX CENTER

2013

JAN 31 2006

Application Serial No. 10/811,728 Revised Appeal Brief dated January 31, 2006

PATENT DOCKET: CU-3663

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT:

Hiroyuki TAKAMURA

SERIAL NO:

10/811,728

) Group Art Unit: 3748

FILED:

March 29, 2004

) Examiner: Ching CHANG

TITLE:

VALVE TRAIN FOR INTERNAL COMBUSTION ENGINE

Certification under 37 C.F.R. §1.8(b)

The USPTO Central Fax No. (571) 273-8300 Date of Fax Transmittal: January 31, 2006

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being transmitted to the United States Patent and Trademark Office to the fax number and on the date indicated above.

15:21

Brian W. Hameder, Reg. No. 45,613

Mail Stop Appeal Briefs – Patent Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

REVISED APPEAL BRIEF

Sir:

In response to the Notification of Non-Compliant Appeal Brief under 37 CFR 41.37 which issued on January 23, 2006, submitted herewith are three (3) copies of Appellant Revised Appeal Brief with respect to the Appeal taken to the Board of Patent Appeals and Interferences in the above-identified application.

The Notification of Non-Compliant Appeal Brief indicated that the Appeal Brief was defective under 37 CFR 41.37 (c)(1)(vi) for not containing a concise statement of each ground for rejection presented for review. The Appellant has revised the Appeal Brief to replace the ~Issues— section heading with a "Grounds of Rejection to be Reviewed on Appeal" section heading.

PATENT DOCKET: CU-3663

Real Party in Interest

The real party in interest is Nippon Piston Ring Co., Ltd. to which full and exclusive interest in the invention of the present application has been assigned. The Assignment, executed March 30, 2004, is recorded in the U.S. Patent and Trademark Office at Reel 014899, Frame 0033.

Related Appeals and Interferences

There are no related appeals or interferences which are believed to directly affect or be directly affected by, or have a bearing on, the Board's decision in the present appeal.

Status of Claims

Claim 1 is pending and appealed. The text of the claims is presented in the Appendix.

Status of Amendments

There are no outstanding amendments. In the Advisory Action issued on July 25, 2005, the amendment to the claims dated July 13, 2005 is indicated as entered for purposes of appeal.

Summary of the Invention

The present application is directed to a valve train in an internal combustion engine having a cam lobe and a roller follower in rotational contact with one another (depicted in Figures 1-3 and 8). The cam lobe is made of a sintered material (Page 4, lines 5-100). The outer circumferential surfaces of both the cam lobe and the roller follower have a surface roughness R_a of 0.4 to 2.2 μ m (Page 4, lines 16-25).

Grounds of Rejection to be Reviewed on Appeal

1. Whether Claim 1 is properly rejected under 35 U.S.C. §103(a) as being unpatentable over Sada (U.S. Patent No. 5,997,988) in view of Nishloka et al. (U.S. Patent No. 6,367,439)?

Grouping of Claims

Claim 1 is the only pending claim.

PATENT DOCKET: CU-3663

<u>Argument</u>

Claim 1 is presently rejected under 35 U.S.C. §103(a) as being unpatentable over Sada in view of Nishioka et al. The Applicant respectfully traverses this rejection and submits that Claim 1 is patentable in view of these relied upon cited references.

The Examiner contends that 'the Sada reference discloses "the present invention is applicable to all machine parts each having a contact surface which enters a state of at least one of rolling contact and sliding contact with the other part opposite thereto" (See Col. 5, line 36 through line 39), and the contact surface having a maximum circumference surface roughness in 1.4 or 1.1 µm (See Table 1). Accordingly, the Examiner deems that the Sada reference teaches each of the cam lobe and the roller in Claim 1, having the claimed subject matter of surface roughness 0.4 to 2.2 µm.' (See the Advisory Action issued July 25, 2005 — Continuation Sheet of 11.). In contrast, the Applicant contends that Sada does not disclose or suggest both machine parts (cam lobe and roller follower) contact surfaces having a <u>surface roughness R_a</u> of 0.4 to 2.2 µm, as claimed.

Table 1 of Sada, on which the Examiner's arguments depend, set forth several embodiments and comparative examples, two of which, embodiment 1 and embodiment 2, disclose a maximum surface roughness Ry on one of the machine part contact surfaces as 1.4 or 1.1 µm. Table 1 does not, however, disclose both machine parts having contact surfaces with these maximum surface roughnesses, or within the claimed Ra surface roughness range of 0.4 to 2.2 µm, as explained in Column 6, line 57 through Column 7, line 11. That excerpt of the reference defines the test set-up that produced the results in Table 1 and clearly indicates that the other machine part has a surface roughness maximum height Ry which equals 3 µm, which is well beyond the claimed range, even if the maximum height Ry surface roughness is the same as the claimed Ra surface roughness, as the Examiner contends and the Applicant disputes. Without question, Sada does not disclose both machine parts having the specified surface roughness, as claimed. The Examiner has gone beyond the disclosure of the reference, and has used improper hindsight, in the assertion that it would have been obvious to provide both machine parts with the claimed surface roughness. This improper assertion of obviousness is even more so in light of the fact that the machine parts in the Sada reference are intended

PATENT DOCKET: CU-3663

to function differently than the cam lobe and follower of the present invention, which will be discussed in more detail later in this argument.

As referred to above, the Examiner also contends that the disclosed maximum height surface roughness R_y in Sada is equivalent to the claimed surface roughness R_a , which is well understood by persons skilled in the art to be the arithmetic mean surface roughness. In support of the Applicant's assertion of the well known definition of R_a . Applicant previously submitted an English translation of Japanese Industrial Standard B 0601 which defines R_a as the arithmetic mean roughness. As shown in Figure 9 of JIS B 0601, R_a is the average of a series of consecutive peak to valley vertical distances over a sample length of a surface. This value of R_a necessarily would be less than R_y which is defined in Sada as the vertical distance between the greatest peak height and the greatest valley height over a sample length of a surface, as shown in Figure 1 of Sada. Thus, Sada does not disclose the claimed R_a surface roughness values.

Also, as referred to above with regard to the function of the invention disclosed in Sada, the function of the prescribed surface roughness is to obtain an oil film controlled by the small recesses in the surface of the machine parts. This purpose is a function of the maximum height R_y surface roughness which is dependent upon and limited by the ratio of the peak height R_p and the valley depth R_v (R_p/R_v , See Figure 1 in Sada). Sada further describes that invention as being applicable to both rolling contact and sliding contact. The goal of that invention is to reduce wear on the machine parts by the formation of the oil film. In contrast, the function of the present invention is to provide only rolling contact between two machine parts without the formation of an oil film. From the stated purpose and function of Sada, the Applicant contends that there would be no motivation to further modify the invention of Sada to perform a different function. No disclosure, teaching or suggestion of such a modification of the function of the device is present, let alone the claimed features of both machine parts having a specified surface roughness.

The Applicant further considers that even if R_a of the present application were equal to R_y of Sada, that Sada teaches away from using the claimed surface roughness, notwithstanding the fact that Sada teaches R_y equals 3 μ m on the second machine part contact surface. Table 1 in Sada shows a R_y value in comparative example 3 within the assumed claimed range that yields a negative result, and a R_y value in embodiment 3 outside the assumed claimed range that

PATENT DOCKET: CU-3663

yields a positive result. This is completely contradictory to the two examples chosen by the Examiner, and further emphasizes that for the purposes of the invention of Sada, R_y is not the determinative value. That being the case, Sada would teach away from the present Claim 1 if both functioned in the same way to produce the same result.

With regard to the cited reference Nishioka et al., this reference is relied upon to provide an example in the prior art where a sintered material is used to manufacture machine parts. This reference is not relied upon by the Examiner, nor considered by the Applicant, to disclose the claimed features of both the cam lobe and roller follower having the prescribed surface roughness of R_a.

Conclusion

For the reasons given above, the Appellant respectfully submits that neither the relied upon cited references of Sada and Nishioka et al. disclose, teach or suggest the claimed features of both the cam lobe and roller follower having a surface roughness R_a of 0.4 to 2.2 μ m. The Appellant thus considers that the Examiner has not met the burden required under 35 U.S.C. §103(a) of proving obviousness in view of these references. Accordingly, the Appellant respectfully requests the Board to reverse the Examiner's rejection of Claim 1, and requests allowance of the application.

January 31, 2006

Date

Respectfully submitted,

Attorney for Applicant Brian W. Hameder c/o Ladas & Parry LLP 224 South Michigan Avenue Chicago, Illinois 60604

(312) 427-1300 Reg. No. 45613

PATENT DOCKET: CU-3663

APPENDIX

Listing of Claims:

- 1. (previously amended) A valve train for an internal combustion engine comprising a cam lobe fixed on a cam shaft and a roller follower provided with a roller to come in rotation-contact with the cam lobe, wherein the cam lobe is made of an iron based sintered material, and the surface roughness R_a of the outer circumferential surface thereof is 0.4 to 2.2 μ m, and the surface roughness R_a of the outer circumferential surface of the roller is 0.4 to 2.2 μ m.
- 2. (cancelled)
- 3. (cancelled)
- 4. (cancelled)